



AB McLAUCHLAN :: WELLIVER METAL

**Service Bulletin #03-88**  
**February 8, 1988**

Attention: Service Manager

RE: Recommended oil for use in Tecumseh, VH-70 Propane Engines, also Honda air cooled Propane Engines.

Propane fueled engines should use an oil with a low Sulfated Ash content. There are several engine oils on the market that are formulated for use in "L.P." or Natural Gas engines. The problems with these oils are that they are only available in either 55 gal. Drum quantity, or 10 w 40 grade.

"Low Ash" has been defined as .5% or less. The oils listed below have the lowest ash content that we have been able to locate, and are available in quart, gallon or 5 gallon containers.

<u>Brand</u>	<u>Grade</u>	<u>Ash Content</u>
UNLOCAL, "PREMIUM"	SAE 30 OR 40	.70
UNLOCAL, "H.D."	SAE 30 OR 40	.73
CHEVRON, "DELO 100"	SAE 30 OR 40	.74
TEXACO, "URSA, E.D."	SAE 30 OR 40	.76
MOBIL, "DELVAC 1100"	SAE 30 OR 40	.85
CHEVRON "DELO 400"	SAE 30 OR 40	.97

10 w 30 oil may be used as an acceptable substitute however, UNDER NO CIRCUMSTANCES, use 10 w 40 grade oil.