


NOTE:

1. WHEN REPLACING REF. NOS. 14 AND 15, CARE SHOULD BE TAKEN TO BE SURE THEY ARE INSERTED IN THE PROPER HOLES. (SEE DIAGRAM BELOW)



REF. NO. 14, (3 REQ) ARE REPLACED AS SHOWN.

16	500-827	O-RING	12
15	500-753	BRASS SEAT ASSY. (SEE NOTE)	9
14	500-752	BRASS CHECK SEAT ASSY. (SEE NOTE)	3
13	500-751	SCREED VALVE W/ HANDLE	1
12	550-427	BALL KNOB	3
11	500-750	GATE VALVE W/ HANDLE	1
10	500-749	HANDLE ASSEMBLY - SCREED	1
9	500-748	HANDLE ASSEMBLY - GATE	1
8	500-747	HANDLE ASSEMBLY - HITCH-ARM	1
7	500-688	HEX HD. CPSCW. 5/16-18 X 4 1/2" LG. GR. 5	4
6	500-743	HEX HD CPSCW. 5/16-18 X 2" LG. GR. 5	8
5	500-746	HITCH-ARM VALVE W/ HANDLE	1
4	500-745	O-RING	3
3	500-744	SELECTOR VALVE MANIFOLD	1
2	500-742	FLUSH PLUG 1/4 NPT SOCK. HD	2
1	500-690	HEX NUT 5/16-18 OVERLOCK	4

LAYTON MANUFACTURING COMPANY
SALEM, OREGON

TITLE
CONTROL VALVE ASSEMBLY

Rev. 2/83

DATE	BY	CHKD	APP'D
11-11-77	None	None	None
REV	DESCRIPTION	REV	DESCRIPTION
1	PAVER F-525	1	500-732 COMPLETE

REV	DESCRIPTION	REV	DESCRIPTION
1	PAVER F-525	1	500-732 COMPLETE