

D-550 'SUPER-PAVER'

①

RIGHT SIDE DEPTH	LEFT SIDE DEPTH	THROTTLE OPEN
RIGHT SIDE EXTENSION	LEFT SIDE EXTENSION	
EXTENSION IN	EXTENSION OUT	NOTICE KEY MUST BE ON BEFORE OPERATING. PROPANE TANK VALVE MUST BE OPEN BEFORE STARTING.
SCREED UP	SCREED DOWN	IN OUT
SCREED LIFT	HITCH ARMS	UP DOWN
ENGINE PRIMER	PRESSURE SWITCH OVERRIDE	OPEN GATE
ELECTRONIC IGN. ON	OFF CLOSED	LEFT AUGER ON RIGHT AUGER ON
MAGENTO IGN. ON		

BUILT UNDER ONE OR MORE OF THE FOLLOWING PATENTS—

U.S. PATENTS	CANADIAN PATENTS
3,515,411, 3,300,341, 286,701	1,361, 286,701
3,298,491, 3,137,451, 287,701	451, 287,701
3,204,101, 3,275,792, 803,711	792, 803,711
3,273,342, 3,238,516, 779,653	516, 779,653
3,330,142, 3,230,710, 803,709	710, 803,709
3,300,211, 3,648,377, 874,034, 856,674	874,034, 856,674
3,704,754, 3,770,318, 933,351, 925,047	933,351, 925,047
3,797,195	

③ **HOLD UP DURING ENGINE STARTING**

④ **ATTENTION**
CHECK ENGINE OIL BEFORE STARTING. CHECK ENGINE OIL EVERY 4 HOURS DURING OPERATION.
—CAUTION—
DO NOT OVERFILL.

⑤ **MAX. TIRE PRESSURE 65 PSI**



⑥


BATTERY INFORMATION

NO. 21F DIMENS (L) (W) (H) 12V/11L 6V/11L 6V/11L

⑦

SHIPPED WITH IHC HYDRAULIC OIL. IF YOU USE, PLEASE USE IHC HYDRAULIC OIL. DO NOT MIX OILS.

⑧



⑨

CAUTION
BEFORE OIL VALVE SHUT OFF
ALL OTHER PROPANE VALVES

⑩

CAUTION
WHEN USING BRIDLE CHAINS TO LIFT IT, BE SURE THEY ARE NOT CAUGHT UNDER THE AUGER

⑪

DECALS

REF. NO.	PART NUMBER	DESCRIPTION	NO. REQ.
1	11761	SHEET OF MISCELLANEOUS DECALS	1
2	500-330	PATENTS	1
3	11982	HOLD UP / STARTING	2
4	11767	ATTENTION CHECK OIL	2
5	11622	TIRE PRESSURE	2
6	500-761	LAYTON MFG. CO.	2
7	11861	BATTERY INFORMATION	2
8	500-350	HYDRAULIC OIL	1
9	550-527	DEPTH INDICATOR SCALE	2
10	12005	PROPANE VALVES, CAUTION	4
11	12013	LIFT CHAINS, CAUTION	2
12	550-364	DECAL SET (INCLUDES ALL THE ABOVE)	2