

NO.		
11512	F525 Paver	(1)
LMC 1622	Tire Pressure	(2)
LMC 11871	Battery Information	(1)
500-350	Oil Spec.	(2)
LMC 11767	Engine Oil Check	(2)
500-330	Patents	(1)
500-761	Layton	(2)
LMC 12013	Bridle Chain	(2)
LMC 12005	Propane Tank	(1)

RIGHT AUGER

LEFT AUGER

PRIMER

ON

OFF

ATTENTION
 CHECK ENGINE OIL BEFORE STARTING. CHECK ENGINE OIL EVERY 4 HOURS DURING OPERATION.
 -CAUTION-
 DO NOT OVERFILL.

NOTICE
 KEY SWITCH MUST BE ON, FOR ELECTRIC POWER TO TOGGLE SWITCHES

BUILT UNDER ONE OR MORE OF THE FOLLOWING PATENTS—

U.S. PATENTS	CANADIAN PATENTS
3,515,411, 3,300,234	837,461, 786,701
3,298,291, 3,138,393	787,651, 787,791
3,304,101, 3,751,174	787,792, 803,211
3,275,342, 3,288,041	777,516, 779,653
3,338,143, 3,330,188	803,210, 803,209
3,409,311, 3,648,871	824,034, 856,674
3,704,754, 3,776,318	933,351, 925,047
3,787,135	

500-310

PUSH TO START

KILL SWITCH

F-525 PAVER

MAX. TIRE PRESSURE 65 PSI

LMC 1622

SHIPPED WITH IHC HY-TRAN OIL, OR THE FOLLOWING CAN BE USED, MOBIL 300 FLUID, SAE10W MS MOTOR OIL. CAUTION: DO NOT MIX OILS.

500-310

BATTERY INFORMATION

NO. 27F-GP-5
 DIMENSIONS

LENGTH	12 1/2 IN.
WIDTH	6 3/4 IN.
HEIGHT	8 3/4 IN.

LMC 11871

CAUTION
 BEFORE OPENING THIS VALVE
SHUT OFF
 ALL OTHER PROPANE VALVES

CAUTION
 WHEN USING BRIDLE CHAINS TO LIFT PAVER, BE SURE THEY ARE NOT CAUGHT UNDER THE AUGER

