


NOTE:

WHEN REPLACING REF. NOS. 14 AND 15, CARE SHOULD BE TAKEN TO BE SURE THEY ARE INSERTED IN THE PROPER HOLES. (SEE DIAGRAM BELOW)



REF. NO. 14, (3 REQ.) ARE REPLACED AS SHOWN.

16	500-109	MALE CONNECTOR	3/16 JIC X 1/4 NPT	2
13	500-753	BRASS SEAT ASSY.	(SEE NOTE)	3
14	500-752	CHECK SEAT ASSY.	(SEE NOTE)	3
13	500-751	SCREENED VALVE W/HANDLE		1
12	500-427	BALL KNOB		3
11	500-750	GATE VALVE W/HANDLE		1
10	500-749	HANDLE ASSY. — SCREEN		1
9	500-748	HANDLE ASSY. — GATE		1
8	500-747	HANDLE ASSY. — HITCH ARM		1
7	500-888	HEX HD. CPSW.	3/16-18 X 4 1/2" LG. GR. 5	4
6	500-743	HEX HD. CPSW.	3/16-18 X 2" LG. GR. 5	8
5	500-746	HITCH-ARM VALVE W/HANDLE		1
4	500-745	O-RING		3
3	500-748	FLUSH PLUG 1/4 NPT SOCK. HD.		2
2	500-744	SELECTOR VALVE MANIFOLD		1
1	500-012	HEX NUT	3/8 - 16	3

LAYTON MANUFACTURING COMPANY
SALEM, OREGON

TITLE:
SELECTOR VALVE ASSEMBLY

140102

REV. A	PART NO.	DESCRIPTION	QTY. REQ.	REV. NO.	PART NO.	DESCRIPTION	QTY. REQ.	DATE	BY
								NONE	5-7-79
									C-307